



CRANE LOAD CHART

| RATED LOAD IN LBS. | | | |
|--------------------|----|------------|-------------|
| | | BOOM ANGLE | STATIC LOAD |
| REACH IN FEET | 5 | 80° | 20,000 |
| | 10 | 78° | 10,000 |
| | 15 | 76° | 6,700 |
| | 20 | 71° | 5,000 |
| | 25 | 65° | 4,000 |
| | 30 | 60° | 3,300 |
| | 35 | 54° | 2,800 |
| | 40 | 48° | 2,500 |
| | 45 | 41° | 2,200 |
| | 50 | 34° | 2,000 |
| | 55 | 24° | 1,800 |
| | 60 | 0° | 1,600 |

COASTAL HYDRAULIC CRANES, INC.
HOUSTON, TEXAS

CRANE MODEL CSA 10-60

MAXIMUM OVERTURNING MOMENT = 353,860 FT-LBS
 MAXIMUM VERTICAL REACTION = 55,700 LBS.
 CRANE WEIGHT = 15,700 LBS.
 MAIN WINCH CAPACITY: 8,000 LBS. (BARE DRUM)
 WINCH SPEED: 50 FPM
 WIRE ROPE CAPACITY: 5,320 LBS.

ALL LIFTS ABOVE 5,320 LBS. REQUIRE 2 OR 3 PARTS OF LINE.

!! WARNING !! DO NOT LOAD BEYOND CRANES RATED CAPACITY.

NOTE: THE ABOVE RATED LOADS DO NOT INCLUDE WEIGHTS OF HOOKS, BALL ETC. TO OBTAIN SWL THESE WEIGHTS HAVE TO BE DEDUCTED FROM THE ABOVE VALUES.

